



Actuator Model Number	B		C	D	E	F	G	H	J	K	DOUBLE ACTING ONLY		VOL / INCH OF STROKE RETRACTED	VOL / INCH OF STROKE EXTENDED	
	A	SR									DA	BASIC WT ZERO STROKE			WT/ INCH OF STROKE
HDH2 (*) DA or SR	11.56	4.38	10.75	2.50	7.00	4	4.13	7.00	0.56	1/4	7/16-14	44	2.82	2.35	3.14
HDH2.5 (*) DA or SR	11.56	4.88	12.75	2.50	7.00	4	4.13	7.00	0.56	1/4	1/2-13	49	2.93	4.12	4.91
HDH3.2 (*) DA or SR	13.69	6.44	16.00	3.25	8.00	4	5.25	9.00	0.69	3/8	5/8-11	81	4.65	6.81	8.30
HDH4 (*) DA or SR	14.81	7.19	18.00	3.75	10.00	4	6.00	10.00	0.69	3/8	3/4-10	124	7.04	10.16	12.57
HDH5 (*) DA or SR	15.06	8.75	20.00	4.00	12.00	4	7.00	12.00	0.94	3/8	1"-8	201	8.47	16.49	19.64
HDH6 (*) DA or SR	19.94	11.50	24.00	4.75	12.00	6	8.00	12.00	0.94	1/2	1"-8	305	10.00	23.37	28.27
HDH7 (*) DA or SR	24.44	12.00	28.00	6.00	15.00	6	9.00	15.00	1.44	3/4	1"-8	556	14.39	31.42	38.48
HDH8 (*) DA or SR	26.56	13.50	32.00	6.75	18.00	6	10.00	18.00	1.69	3/4	1 1/8-12	827	17.59	40.64	50.27
HDH10 (*) DA or SR	32.31	15.63	O/A	8.75	18.00	8	12.00	18.00	1.94	3/4	1 1/8-12	1254	22.57	62.64	78.54
HDH12 (*) DA or SR	37.75	18.38	O/A	9.75	18.00	8	13.00	18.00	1.69	3/4	1 1/4-12	1756	31.67	97.19	113.10
HDH14 (*) DA or SR	40.69	20.38	O/A	9.75	18.00	8	14.00	19.00	1.94	3/4	1 1/2-12	2262	42.08	130.18	153.94
HDH16 (*) DA or SR	41.63	23.88	O/A	9.75	18.00	8	14.00	19.00	1.94	3/4	1 1/2-12	2908	44.23	177.3	201.06

(*) Denotes actuator stroke (O/A) Denotes On Application

CONSULT FACTORY FOR OVERALL LENGTH AND WEIGHTS FOR SPRING RETURN MODELS VOLUME IS IN CUBIC INCHES, DIMENSIONS ARE IN INCHES, WEIGHTS ARE IN POUNDS (LBS). LIFTING EYES ARE AVAILABLE FOR DOUBLE ACTING MODELS 10 THRU 16. LIFTING EYES ARE STANDARD FOR SPRING RETURN MODELS