



Actuator Model Number	A	B	C	D	E	F	G	H	J	K	L	M	DOUBLE ACTING ONLY		VOL / INCH OF STROKE RETRACTED	VOL / INCH OF STROKE EXTENDED
													BASIC WT ZERO STROKE	WT/ INCH OF STROKE		
HDL4 (*) DA or SR	9.44	6.25	2.50	7.00	4	3.122	7.00	0.44	1/4	3.88	3/8-16	2.298	48	2.74	11.78	12.57
HDL5 (*) DA or SR	9.44	7.25	2.50	7.00	4	3.122	7.00	0.44	1/4	3.88	3/8-16	2.298	55	2.76	18.85	19.64
HDL6 (*) DA or SR	9.44	8.25	2.50	7.00	4	3.122	7.00	0.44	1/4	3.88	3/8-16	2.298	67	3.08	27.49	28.27
HDL7 (*) DA or SR	9.44	9.25	2.50	7.00	4	3.122	7.00	0.44	1/4	3.88	3/8-16	2.298	79	3.45	37.70	38.48
HDL8 (*) DA or SR	12.63	10.13	3.75	8.00	4	5.000	10.00	0.56	3/8	5.59	5/8-11	2.500	146	4.81	47.86	50.27
HDL10 (*) DA or SR	13.25	12.50	3.75	8.00	4	5.000	10.00	0.56	3/8	5.59	5/8-11	2.500	201	5.35	76.13	78.54
HDL12 (*) DA or SR	13.05	15.00	3.75	9.00	4	-	10.50	0.61	1/2	5.83	5/8-11	-	269	6.15	110.69	113.10
HDL14 (*) DA or SR	17.50	17.00	4.75	12.00	6	-	9.38	0.69	1/2	6.50	3/4-10	-	427	9.11	149.03	153.94
HDL16 (*) DA or SR	17.50	19.25	4.75	12.00	6	-	12.00	0.69	1/2	6.50	3/4-10	-	508	10.8	196.15	201.06
HDL18 (*) DA or SR	17.50	21.38	4.75	12.00	6	-	12.00	0.69	1/2	6.50	3/4-10	-	596	11.71	249.56	254.47
HDL20 (*) DA or SR	20.00	23.25	6.00	12.00	6	-	12.00	0.94	3/4	8.50	1"-8	-	818	15.19	307.09	314.16
HDL22 (*) DA or SR	20.00	25.75	6.00	12.00	6	-	12.00	1.19	3/4	8.50	1"-8	-	974	16.46	373.07	380.13
HDL24 (*) DA or SR	21.38	27.75	6.75	18.00	8	-	19.00	1.19	3/4	15.00	1"-8	-	1359	22.25	442.77	452.39
HDL26 (*) DA or SR	21.38	30.25	6.75	18.00	8	-	19.00	1.19	3/4	15.00	1"-8	-	1570	23.69	521.31	530.93
HDL28 (*) DA or SR	21.38	32.25	6.75	18.00	8	-	18.00	1.19	3/4	15.00	1"-8	-	1697	24.58	606.13	615.75
HDL30 (*) DA or SR	21.88	34.50	6.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	1986	26.09	697.24	706.86
HDL32 (*) DA or SR	28.50	36.50	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	2326	28.77	788.35	804.25
HDL34 (*) DA or SR	29.50	38.50	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	2929	30.55	892.02	907.92
HDL36 (*) DA or SR	29.50	40.50	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	3144	31.44	1001.97	1017.88
HDL38 (*) DA or SR	29.50	43.00	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	3484	32.86	1118.21	1134.12
HDL40 (*) DA or SR	30.00	45.13	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	4005	35.00	1240.74	1256.64
HDL42 (*) DA or SR	30.00	47.13	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	4319	35.89	1369.54	1385.45
HDL44 (*) DA or SR	31.00	49.13	8.75	18.00	8	-	18.00	1.19	1	15.00	1"-8	-	5151	36.78	1504.63	1520.53

(\*) Denotes actuator stroke

CONSULT FACTORY FOR OVERALL LENGTH AND WEIGHTS FOR SPRING RETURN MODELS VOLUME IS IN CUBIC INCHES, DIMENSIONS ARE IN INCHES, WEIGHTS ARE IN POUNDS (LBS). LIFTING EYES ARE AVAILABLE FOR DOUBLE ACTING MODELS ON REQUEST (4" BORE THRU 16" BORE) 18" THRU 44" BORE LIFTING EYES ARE STANDARD